

NCR iTRAN 180e and 300e

Looking for high-performance item processing at an affordable price?

YES

Designed for reliability, accuracy and efficiency

These are multipurpose, low to medium speed transports that can be configured for a wide variety of item processing applications (including capture, proof of deposit, remittance processing or reject re-entry). Designed and built for maximum wall-clock performance, the hardware interface and platform middleware (NCR's WiselP) guarantee speedy operator recovery of document jams or media replacement. Featuring ergonomic design and long-term reliability, these transports are designed to be user-friendly.

- **Maximum productivity with superior technology**

Built to cope with the demands of high-volume, the NCR iTRAN 180e and 300e have the capabilities to efficiently and cost effectively process daily volumes from 15,000 to 75,000 items per day. The iTRAN 180e is rated at 180 dpm*, the iTRAN 300e is rated at 300 dpm*.

- **Lets you offer better service to customers**

Both transports use cutting edge technology and software to give users an array of system and performance data – accessed via a user-friendly interface. In turn, this lets you offer improved servicing and faster transaction times to customers.

- **Long-term reliability keeps downtime to a minimum**

NCR has a proven track record for creating durable hardware that operates reliably, hour after hour. This gives you the peace of mind to make the most of every feature from day one.

- **Easy maintenance for increased productivity**

We know that even short periods of downtime can result in significant loss of revenue. To avoid this, NCR iTRAN 180e and 300e have been designed for quick maintenance, with detailed diagnostic reporting and easily-accessed modular components.

- **The latest optics reduce operator interventions**

Utilizing advanced digital camera technology the image quality in all formats is superb. The file size and resolution can be optimized for each application you use.



iTRAN 180e



iTRAN 300e

For more information, visit www.ncr.com,
or email financial@ncr.com.



Experience a new world of interaction

NCR iTRAN 180e and 300e

Key Features

- Auto feed hopper holds up to 1,200 documents
- Supports MICR, dual MICR, OCR and MICR/OCR combinations
- Thermal encoder (100dpm), High speed encoder (300dpm, only available on 300e)
- Graphical endorser
- High quality color image capture
- Up to 10 pocket modules (4 pockets per module), 40 pockets

Why NCR?

With over 40 years of experience and knowledge, NCR is the leading global provider of payments, assisted- and self-service solutions. NCR has been the global number one manufacturer of ATMs for more than 22 consecutive years. We help our clients around the world improve their customer interactions, implement change quickly and proactively, and transform their businesses to become leaders and change agents. We can help you, too.

Technical Specifications

PRODUCT DIMENSIONS

HEIGHT

- | | | |
|-----------------|-------|-----------|
| • Base Module | 55.0" | (1,357mm) |
| • MICR Verifier | 39.0" | (980mm) |
| • Pocket Module | 34.0" | (860mm) |

DEPTH

- | | | |
|-----------------|-------|---------|
| • Base Module | 32.5" | (825mm) |
| • MICR Verifier | 28.0" | (708mm) |
| • Pocket Module | 28.0" | (708mm) |

LENGTH

- | | | |
|-----------------|-------|-----------|
| • Base Module | 74.0" | (7,880mm) |
| • MICR Verifier | 14.0" | (355mm) |
| • Pocket Module | 17.5" | (443mm) |

WEIGHT

- | | | |
|-----------------|--------|---------|
| • Base Module | 610lbs | (277kg) |
| • MICR Verifier | 101lbs | (46kg) |
| • Pocket Module | 98lbs | (45kg) |

DOCUMENT DIMENSIONS

- The transports are capable of handling documents that meet the following criteria:
- Length – min: 4.75" (121mm), max*: 9.0" (228mm)
- Height – min: 2.5" (65mm), max*: 4.8" (123mm)
- Thickness – min: 0.003" (0.075mm), max*: 0.0075" (0.190mm)
- Weight – min: 20lbs (75g/m²), max*: 28lbs (105g/m²)

PERFORMANCE TRACK SPEED

- iTRAN 180e – 180 "burst" dpm
- iTRAN 300e – 300 "burst" dpm

FLAT-SCREEN MONITOR

- Flat-screen LCD color monitor on swivel stand
- Optional touchscreen version

DOCUMENT FEEDER

- Standard auto feed hopper – 1,200 document capacity
- Hand-drop feeder
- Merge hopper (optional) - 150 document capacity

READER

- Dual-font reader, MICR: E13B and CMC7, OCR: OCR A/B numeric and alphanumeric, up to 10 fonts available (3 user-defined zones)

ECR-ENHANCED CODELINE RECOGNITION

- Optional software that combines E13B codeline data from MICR and OCR to provide a "best read" result
- Runs at full track speed

IMAGING MODULE

- Choose From: upstream and/or downstream image camera, color imaging, black-and-white CCITT, grayscale JPEG, up to 2 image formats per camera, resolutions: 100, 120, 160, 200, 240, 300dpi

ENCODER

- Low-speed - 100dpm (single path), MICR: E13B, CMC7, OCR A/B
- High-speed – 300dpm (single path), MICR: E13B or CMC7

ENDORSER

- Dot Matrix - 180dpm for iTRAN 180e, up to 230dpm for iTRAN 300e, programmable, rear dual line, up to 160 characters per document
- Graphical – optional rear only or front and rear, up to 180dpm for iTRAN 180e, up to 300dpm for iTRAN 300e, programmable, up to 8 user-defined bit-maps, 1 to 4 lines of standard print (up to 180 characters per document)

POCKETS

- 4 pockets per module – each pocket has 300 document capacity
- Up to 10 modules for a total of 40 pockets

PC CONTROLLER (MINIMUM)

- Each iTRAN 180e or iTRAN 300e requires a dedicated PC controller
- NCR certified PCs are recommended

COMMUNICATIONS

- Ethernet LAN for external interface
- RIAB Board (included with imaging)

POWER REQUIREMENTS

- The transport requires a dedicated single-phase power source
- Voltage range: 100-240 volts
- Frequency range: 50Hz to 60Hz

* Preferred document specification are available in the NCR iTRAN 180e and 300e product information publication



Experience a new world of interaction

NCR iTRAN 180e and 300e

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

NCR iTRAN is either a registered trademarks or trademarks of NCR Corporation in the United States and/or other countries. All brand and product names appearing in this document are trademarks, registered trademarks or service marks of their respective holders.

© 2008 NCR Corporation Patents Pending

EB5884-0908

www.ncr.com